



# R-10404

## Gap Filler

### Thermal Interface Materials

Saint-Gobain Performance Plastics **ThermaCool™ R-10404** is a thermally conductive closed cell silicone sponge rubber. This material offers thermal conductivity along with electrical isolation. R-10404 is the superior choice for gasketing and cushioning applications requiring critical thermal transfer, sealing.

### Physical Properties

Property	Test Method	R-10404
Color	Visual	Light Green
Thickness, nominal (inch)	ASTM D374	1/32, 1/16, 3/32, 1/8, 3/16, 1/4
Thermal Conductivity (W/mK)	ASTM E1530	see chart below
Thermal Impedance (°C in. <sup>2</sup> /W)	ASTM E1530	see chart below
Break Strength (psi)	ASTM D412	120
Elongation (%)	ASTM D412	150
Hardness (Shore A)	ASTM D2240	13
Dielectric Strength (volts/mil)	ASTM D149	100
Compression Deflection (@25%, psi)	ASTM D1056	20
Compression Set	ASTM D1056	15
Density (lbs./in. <sup>3</sup> )	ASTM D297	0.040
Operating Temperature (°F)	—	-80 to 400

Compression (%)	Pressure (psi)	Thermal Conductivity (W/mK)	Thermal Impedance (°C in. <sup>2</sup> /W)
Contact	<1	0.30	6.0
10	5	0.40	4.5
25	12	0.45	2.5
50	34	0.65	1.0

All properties are typical values and should not be used for writing specifications.

### Recommended Uses

R-10404 is offered to fill the needs of an unsupported thermal transfer material in applications requiring clean release, enhanced thermal performance by filling air gaps, electrical isolation and vibration cushioning.

### Availability

R-10404 is available in both sheets 36"x 36" and yard goods 36" wide. Material can be supplied with an aggressive acrylic pressure sensitive adhesive or high temperature silicone adhesive on one side. Non-standard thicknesses available, please consult with factory. Extra firm grade also available in 1/32" thickness.

**Limited Warranty:** For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

**NOTE:** Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

### Features/Benefits

- Excellent Conformability to irregular surfaces
- Clean release from most materials
- Repositionable
- Die Cuttable
- Multiple thicknesses to fill various air gap heights
- Foam structure provides extremely compliant gap filler
- Cost effective thermal gap filler

### Applications

- Electronic Modules for Power Devices for Power Supplies
- Computers
- Telecommunication
- Automotive Electronics
- Electrical Insulation
- Military
- Medical
- Heat Pipe Assemblies
- CD ROM Cooling
- Vibration mounts
- Press pads
- Decal transfer

©2004 Saint-Gobain Performance Plastics Corporation  
AFF-1280-PDF-1104-SGCS