



TECHNICAL DATA SHEET

SNE-560- UL94VO



SNE-560-UL94VO | 60 Durometer Conductive Silicone Rubber with Nickel / Graphite Filler

SNE-560-UL94VO is a silicone polymer with nickel-coated graphite particulate fill; giving it very good shielding and grounding properties. High performance and competitively priced, SNE-560-UL94VO makes an excellent option for commercial and military EMI applications. SNE-560-UL94VO is flame rated.

Stockwell Elastomerics offers pre-production and full production parts made from SNE-560-UL94VO, including waterjet cutting, die cutting, and molding. 3M conductive adhesive backing is also available for cut parts and select molded parts.

SNE-560-UL94VO Details

Testing	Specification
Durometer, Shore "A" (+/-5)	60
Volume Resistivity, ohm-cm	1.0 max (0.3 typical)
Shield effectiveness, 20MHz-10GHz	> 117 dB**
Tensile Strength, psi	150 min
Elongation %	100 min
Tear "B", ppi	70
Temperature Low, °C (°F)	-60 (-76)
Temperature High, °C (°F)	220 (428)
UL-94 Flammability Rating	VO*
Specific Gravity	2.0

Additional Specifications

- Available Colors: Gray
- Available Configurations: Sheets, Cut Parts (Waterjet, Die Cut), Conductive Adhesive Backed, Molded Parts
- MIL-DTL-83528 Not Applicable

Scan To Learn More:



*Additional data available upon request.

** Shielding data was run third party at a MIL-DTL-83528 listed lab.

Stockwell Elastomerics, Inc.
4749 Tolbut St. Philadelphia, PA 19136-1512 USA
800.523.0123 | 215.335.3005

100% Employee Owned
AS9100 | ISO9001 Certified
www.stockwell.com | service@stockwell.com

