



TECHNICAL DATA SHEET

SNE-540



SNE-540 | 40 Durometer Conductive Silicone Rubber with Nickel / Graphite Filler

SNE-540 is a silicone polymer with nickel-coated graphite particle fill giving it very good shielding and grounding properties. High performance and competitively priced, SNE-540 makes an excellent option for commercial and military EMI applications.

Stockwell Elastomerics offers pre-production and full production parts made from SNE-540, including waterjet cutting, die cutting or molding. 3M conductive adhesive backing is also available for cut parts and select molded parts.

SNE-540 Details

Property	Typical Value
Durometer, Shore "A", (+/- 5)	40
Volume Resistivity, ohm-cm	0.03
*Shielding Effectiveness, dB	>100 (@ 20MHz - 10GHz)
Tensile Strength, minimum, psi	120
Elongation at break (%), minimum	200
Tear "B", min ppi	40
Temperature Low, °C (°F)	-60 (-76)
Temperature High, °C (°F)	220 (428)
Specific Gravity	1.90

Additional Specifications

- Available Colors: Black
- Available Configurations: Sheets, Cut Parts (Waterjet, Die Cut), Conductive Adhesive Backed, Molded Parts
- MIL-DTL-83528 Not Applicable.

Scan To Learn More:



*Additional data available upon request. 3rd party tested, method: MIL-DTL-83528D

Stockwell Elastomerics, Inc.
4749 Tolbut St. Philadelphia, PA 19136-1512 USA
800.523.0123 | 215.335.3005

100% Employee Owned
AS9100 | ISO9001 Certified
www.stockwell.com | service@stockwell.com

