

STOCKWELL ELASTOMERICS MANUFACTURING SOLUTIONS THROUGH ENGINEERED MATERIALS

Product: EMI Gasket Materials



https://www.stockwell.com/emi-gaskets/

Design & Engineering

Staff engineers comprehend design challenges and are available to help select materials and manufacturing processes that best fit specific application needs.

Material Solutions

Stockwell Elastomerics has strategically partnered with industry leaders such as Rogers Corp., Saint-Gobain, 3M, Wacker Silicones and Momentive Silicones to ensure the highest quality materials are used. Stockwell Elastomerics has a comprehensive inventory of engineered materials designed and manufactured to meet requirements of the most demanding gasketing applications.

Pre-Production through Manufacturing

Combining in-house CNC die cutting, waterjet cutting, injection molding, compression molding and adhesive lamination with comprehensive inventory, Stockwell Elastomerics can fulfill fast-turn prototyping, pre-production and full production requirements.

SNEF-60

Compound: 60 Durometer Conductive Fluorosilicone Rubber with Nickel / Graphite Filler

Product Description:

SNEF-60 is a fluorosilicone polymer with nickel coated graphite particle fill, giving it very good shielding and grounding properties with added chemical resistance due to the fluoropolymer. High performance and competitively priced, SNEF-60 makes an excellent option for commercial and military EMI applications.

Stockwell Elastomerics offers pre-production and full production parts made from SNEF-60, including waterjet cutting, die cutting or molding. 3M conductive adhesive backing is also available for cut parts and select molded parts.

Property	Typical Value
Durometer, Shore "A", (+/- 5)	60
Volume Resistivity, ohm-cm	0.04
Tensile Strength, minimum, psi	200
Elongation, min %	200
Tear "B", min ppi	35
Temperature Low, °C (°F)	-60 (-76)
Temperature High, °C (°F)	200 (392)
Specific Gravity	2.20
Color	Dark Grey
Mil-G-83528	N/A
Available Configurations	 Sheets Cut Parts (Waterjet/Die Cut) Molded Parts Conductive Adhesive Backed