

# ThermaCool® TC3006

Saint-Gobain Performance Plastics **ThermaCool® TC3006** is an extremely soft ceramic-filled silicone elastomer typically supplied with a PET release liner on both sides. The product is intrinsically tacky and can be compressed over a wide range of stack up tolerances with minimal force applied to component parts. TC3006 can be supplied with a fabric or film on one side for additional support during handling and assembly.

## Physical Properties

Property	Test Method	TC3006
Color	Visual	Light Green
Thickness, nominal (in)	ASTM D374	0.020 - 0.250
Thermal conductivity (W/mK)	ASTM D5470	1.1
Thermal impedance (°C in <sup>2</sup> /W)	ASTM D5470	See data below
Hardness (Shore 00)	ASTM D2240	< 35
Dielectric strength (volts/mil)	ASTM D149	> 250
Volume resistivity (ohm-cm)	ASTM D257	2.03 x 10 <sup>10</sup>
Operating temperature (°F)	-	-65 to 392
UL listing recognition	UL94	V-0

All properties are typical values and should not be used for writing specifications.

Data reflects non-supported option.

## Compression-Deflection Data

Deflection force is recorded after a one minute dwell time at the compression setting.

	Percent	Deflection Force (psi)	Thermal Impedance (°C in. <sup>2</sup> /W)
TC3006	10	1	3.22
0.1 in	30	7	2.51
	50	15	1.79

## Recommended Uses

- Any gap filler application with large component height differences that are covered with a single pad.
- Typical used in memory cards, VGA modules and other multiple components assemblies.

**Limited Warranty:** For a period of 6 months from the date of first sale, Saint-Gobain Performance Plastics Corporation warrants this product(s) to be free from defects in manufacturing. Our only obligation will be to provide replacement product for any portion proving defective, or at our option, to refund the purchase price thereof. User assumes all other risks, if any, including the risk of injury, loss or damage, whether direct or consequential, arising out of the use, misuse, or inability to use this product(s). SAINT-GOBAIN PERFORMANCE PLASTICS DISCLAIMS ANY AND ALL OTHER WARRANTIES, EXPRESSED OR IMPLIED, INCLUDING THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

**NOTE:** Saint-Gobain Performance Plastics Corporation does not assume any responsibility or liability for any advice furnished by it, or for the performance or results of any installation or use of the product(s) or of any final product into which the product(s) may be incorporated by the purchaser and/or user. The purchaser and/or user should perform its own tests to determine the suitability and fitness of the product(s) for the particular purpose desired in any given situation.

## Silicone Gap Filler Thermal Interface Materials

### Features

- Extremely soft and compliant gap filler
- Integral support using fabric or PET film
- Fabric support provides good cut resistance for high abuse applications

### Benefits

- Very low pressure applied to assembled components
- Useful for spanning multiple components with different heights to minimize force on joints
- Improve die-cutting and part stability while handling

### Availability

- 24" x 24" sheets in thicknesses from 0.020" to 0.250"
- Available with fabric or film reinforcements
- Tacky surfaces are available on one or both sides

**Saint-Gobain Performance Plastics Corporation**  
14 McCaffrey St.  
Hoosick Falls, New York 12090-0320  
Customer Service: (800) 962-2666  
Tel: (518) 686-7301  
Fax: (800) 562-8479, (518) 686-4840

Avenue du Parc 18  
B4650 Chaineux, Belgium  
Tel: (32) 87-32-20-11  
Fax: (32) 87-32-20-51

[www.foams.saint-gobain.com](http://www.foams.saint-gobain.com)

ThermaCool® is a registered trademark  
SPES168-PDF-0412